



BioLoc Tx, hybrid and light weight

SPECIFICATIONS



Weight and dimension	10grs – 30*21*8 mm	26grs – 50*26*15 mm	21grs – 45*29*18 mm	Adjustable
Network	BioLoc base station in 434MHz	BioLoc base station in 434MHz	BioLoc base station in 434MHz Argos in Geofencing mode	BioLoc base station in 434MHz
GNSS receiver	GPS/GAL/GLO/BDS/QZSS	GPS/GAL/GLO/BDS/QZSS	GPS/GAL/GLO/BDS/QZSS	GPS/GAL/GLO/BDS/QZSS
Internal sensors	Temperature Battery level	Temperature Accelerometer 3-axis Battery level	Temperature Accelerometer 3-axis Battery level	Temperature Accelerometer 3-axis Battery level
Memory	Nonvolatile 1Mbits	Nonvolatile 1Mbits	Nonvolatile 1Mbits	Nonvolatile 1Mbits
Autonomy	600 fixes	3000 fixes	Illimited – Solar energy	40grs - 2100 fixes 50grs - 3000 fixes 80grs - 6000 fixes 120grs - 14000 fixes
Compatibility	BioLoc Rx	BioLoc Rx	BioLoc Rx Argos in Geofencing mode	BioLoc Rx